

## TBUS-6xI

Table Mount Modular Multi-Connection Solution - Manually Retracting Lid



The TBUS-6xl is the enclosure of a new modular system with a tilt-up lid. A complete TBUS system requires the enclosure, an inner frame, a power socket, inserts and a power cord.

NOTE: The TBUS enclosure, power socket, power cord & inserts are purchased separately

## **FEATURES**

Inner Frame - 3 different "T3F" inner frame options are available that can accommodate a combination of up to 4 power sockets, 6 cable pass-through or connector inserts, 1 long insert and up to 3 Kramer TOOLS

Power Sockets - 8 different "TS" single power socket options are available to accommodate the power requirements worldwide

Power Cord - 8 different "C-AC" single power cords (and 3 "Y" power cords) for each power socket Optional Accessories - TBUS Brackets, K-Able Box Cable Reels, Step-In Modules and Controllers are available

Retractable Lid - Manually slides into unit

Connector Depth - Adjustable

Installation Requirement - Table cutout of 225mm x 123mm (8.87" x 4.85")

Dimensions - Top plate:  $24.3 \text{cm} \times 14.0 \text{cm} (9.6" \times 5.5") \text{ W}$ , D; Enclosure:  $22.1 \text{cm} \times 10.2 \text{cm} \times 13.0 \text{cm} (8.7" \times 4.0" \times 5.1") \text{ W}$ , D, H

Weight - 1.35 kg (2.8 lbs) approx.; table clamps: 0.25 kg (0.6 lbs) approx



## TECHNICAL SPECIFICATIONS

INCLUDED Power cord, table clamps, self locking ties, template, template screws

ACCESSORIES:

OPTIONS: Insert kit

Product Dimensions 24.30cm x 13.40cm x 14.00cm (9.57" x 5.28" x 5.51") W, D, H

Product Weight 0.0kg (0.0lbs) approx

Shipping Dimensions  $36.00cm \times 26.50cm \times 21.00cm (14.17" \times 10.43" \times 8.27")$  W, D, H

Shipping Weight 0.0kg (0.0lbs) approx



## CONFIGURATIONS

TBUS-6xI(B)	Enclosure - Black Sand Blasted Anodized Aluminum Top
TBUS-6xI(BC)	Enclosure - Silver Sand Blasted Anodized Aluminum Top

